



散裝電容成型機

Loose Radial Lead Forming Machine

電壓 Power: AC 220V 50 / 60HZ

機器尺寸 Dimension: 860 × 1370 × 1500mm

重量 Weight: 350KGS

氣壓 Air pressure: 4 ~ 5Kg / cm²

加工量 Capacity: 40~150pcs / Minute

三種機型 Three Models: 可處理直徑φ4mm~φ20mm之零件

CF-408 Former-φ4~φ8mm

CF-1013 Former-φ10~φ13mm

CF-1620 Former-φ16~φ20mm

成型腳距: 2.5~25mm皆可適用。

自動功能: 入料、夾料、成型、切腳、完成退料
全自動化連續作業，一次完成。

成型範圍: 原材料只要能由送料機，排列入料，本機就能自動成型，
功能很強。

成型樣式: 直線，內彎，外彎，前後彎，成型90度如有特殊形狀，可
按圖或照樣品製作。

自動送料機: CF-0408使用單型盤CF-1013 & CF-1620使用子母盤送料。

傳動機構: 使用凸輪及氣缸搭配，精確穩定耐用零件、模具標準化，
更換容易。

電控系統: 電腦化操作簡易功能強，無段變頻調速。

功能設定: 成品自動計數，可直接包裝。

Component Pitch: 2.5~25mm available.

Procedure: Feed, hold, form, cut, finish and retreat materials
automatically at a time.

Die and module are customized upon drawing with
specification.

Range: Any stand-up materials that can align in a line can be formed
automatically.

Apply for wide range of parts, it is a powerful machine.

Forming type: Straight, inward kinks, outward kinks, opposite kink,
90-degree bend and special forming shape can be
tailored according to drawing or samples.

Feeder: CF-0408 uses single feeder..

CF-1013 & CF-1620 use twin feeders.

Transmission: Cams and air cylinder operate accurately, stably and
durably. Standardized spare parts are easy to change .

Electronic system: Computerized control panel and powerful function
are helpful.

Speed control is stepless frequency.

Function set up: Count during production. Packing directly after compliment.

CF-408
CF-1620
CF-1013

