



直線式基板插件線輸送機 PCB INSERTION CONVEYOR

此種輸送機機身為三公尺一個單位，機身寬度可隨基板大小調整，架設容易，彈性大，可隨工位多少變化生產線流程。

The machine body is mainly made up of 3m sections. The machine body's width is adjustable with the size of the base plate. It is easily installed with great flexibility, it can follow the extend of changes in the production.



直線插件線
STRAIGHT INSERTION C/V



寬 WIDTH	550mm
高 HEIGHT	750 ± 20mm 作業線 750 ± 0° ~ 15° 銜接線 750 ± 20mm Operation Line. 750 ± 0° ~ 15° Connection
長 LENGTH	2000mm 3000mm 兩種可隨地形配合連接 Line, 2Kinds of 2000mm and 3000mm which can be connected depend on to pography.
電路板有效可調電度 P.C.B. Effective/Adjustable	60—300mm 手搖桿操作 60—300mm Manual Swing Rocker.
輸送速度 Conveying Speed	V = 0.2 ~ 2M / MIN
附屬配件 Accessories	照明、作業說明書掛架、零件盒架，焊錫後直接入皮帶輸送機上檢修 Hanger Frame For Lighting Operation Manual Parts Box Frame, After Tin soldering, directly put on the belt for conveying Inspection / Maintenance on machine.